DATA SHEET

FULBANK 2000



www.fulbat.com - • FULBAT







- CHARGES AND MAINTAINS 3 BATTERIES WITH DIFFERENT VOLTAGE AND CHEMISTRIES AT ONCE
- 2A PER BANK WITH CAPACITY UP TO 40AH (120AH IN MAINTENANCE)
- FOR ALL BATTERIES: GEL, AGM, MF, DRY, WET & LIFEPO4
- EASY TO READ LED DISPLAY
- FULL PROTECTED AGAINST SHORT CIRCUIT, WRONG CONNECTIONS, OVERCHARGE AND OVERHEAT
- SPLASH AND DUST PROOF (IP65)
- DELIVERED WITH 3 CLAMPS AND 3 FUSED CONNECTION SET

AUTOMATIC SMART BATTERY BANK CHARGER & MAINTAINER

SPECIFICATION

6v/12v

STAGES

4

CURRENT

3x2a

BATTERY

4_{Ah} > 40_{Ah}

TECHNOLOGY COMPATIBILITIES













CHARGING FEATURES

CHARGING FEATURES
FULBANK 2000 - 4 STAGES

Voltage (1)
Current (A)

BATTERY CHECK
6V /12V detection Reduces charging time by delivering maximum charge to set voltage. Reduces charging time by delivering maximum charge to set voltage.



